

P2381Y-P4



Product characteristics


- 23.8-inch LCD, 1920*1080, 16:9, capacitive touch screen
- 1*HD OUTPUT
- 5*Intel I210 Gigabit network cards, four of which support POE
- 4*RS232 serial port, COM1~2 RS232 DB9 serial port, COM2 support RS485/422, COM3~4 RS232 on the 2*12P Phoenix terminal, COM3 support RS485
- 4 in and 4 out GPIO, 2*USB3.0, 2*USB2.0
- 9~36V wide voltage input
- Aluminum alloy material, fanless cooling structure
- Support 1* SIM card slot

Model number	P2381Y-P4 V1.0	
chassis	Material/Structure	Aluminum alloy material, fanless cooling structure
	colour	Bright silver
	Dimensions (length, width and height)	W364.5 L584.5 * H64.7 mm
	Weight (bare weight)	8.6 KG
	Install	Wall Mount /VESA
LCD screen	type	23.8-inch full HD, 16:9 widescreen
	Resolution	1920 * 1080
	luminance	300cd/m2
Touch screen	type	Capacitive. 10-point touch (adjustable resistance screen)
	Light transmittance	More than 85%
IO interface	POWER	1* Power key, 1* one key restore (and reset key to choose one), 1*CMOS reset key, 1*ACLOSS (power on DIP switch)
	Display interface	1*HD OUTPUT
	LAN	5*Intel I210 Gigabit network cards, four of which support POE
	USB	2 * USB3.0, 2 * USB2.0
	Audio frequency	1*AUDIO, Line out and MIC in one
	COM	4*RS232 serial port, COM1~2 RS232 DB9 serial port, in which COM2 supports RS485/422, COM3~4 RS232 on the 2*12pin Phoenix terminal, in which COM3 supports RS485, COM1-2 supports the 9pin live function
	Phoenix terminal	2*12Pin(4 in 4 out GPIO, switching signal, COM3~COM4, 5V VCC and GND)
	Dip switch	10-bit dip switch, COM2 to 3 RS232/485 switch, COM2 RS422 through the COM2_SW1 jumper


	Power source	1*DC (5.5*2.5) air port or 1*2P P=5.08mm Phoenix terminal, support 9V~36V input
store	SATA	1 x 2.5-inch hard disk
	MSATA	1*MSATA
	M.2	1*M.2/SSD: Key-M, 2280, NVME PCIe4 SSD
extend	M.2	1*M.2/WiFi, Key-E, 2230, supports the WiFi module
		1*M.2/5G, Key-B, 2242/52, supports the 5G module
Power demand	Power supply type	External power adapter
	Voltage input	9V~36V wide voltage
	Power output	60W~120W
environment	Operating temperature	0°C to 50°C
	Storage temperature	-20°C ~ 70°C
	Relative humidity	5%-95% relative humidity, no condensation
	Working vibration	0.5g rms/5-500HZ/random/operating




尺寸图



前面板视图



后面板视图



底部I/O视图



工业平板

所有产品规格变更，均不另行通知

订货信息

No.	Model	CPU	Memory	Motherboard	IO Board	GPIO	LAN	COM	HD OUTP	USB 2.0	USB 3.0	power
1	P2381Y-P4 V1.0(7300U)	I5-7300U/2.6G	2*SODDDR4	P68	P1082-P4/P177-IO/P1071-LED	4进4出	5	4	1	2	2	9~36V
2	P2381Y-P4 V1.0(8260U)	I5-8260U/1.6G	2*SODDDR4	P81	P1082-P4/P177-IO/P1071-LED	4进4出	5	4	1	2	2	9~36V
3	P2381Y-P4 V1.0(10210U)	I5-10210U/1.6G	2*SODDDR4	P102	P1082-P4/P177-IO/P1071-LED	4进4出	5	4	1	2	2	9~36V
4	P2381Y-P4 V1.0(1135G7)	I5-1135G7/2.4G	2*SODDDR4	P112	P1082-P4/P177-IO/P1071-LED	4进4出	5	4	1	2	2	9~36V
5	P2381Y-P4 V1.0(1235U)	I5-1235U/1.3G	2*SODDDR4	P122	P1082-P4/P177-IO/P1071-LED	4进4出	5	4	1	2	2	9~36V
6	P2381Y-C6 V1.0(7300U)	I5-7300U/2.6G	2*SODDDR4	P68	P1082-C6/P177-IO/P1071-LED	4进4出	2	6	1	2	4	9~36V
7	P2381Y-C6 V1.0(8260U)	I5-8260U/1.6G	2*SODDDR4	P82	P1082-C6/P177-IO/P1071-LED	4进4出	2	6	1	2	4	9~36V
8	P2381Y-C6 V1.0(10210U)	I5-10210U/1.6G	2*SODDDR4	P102	P1082-C6/P177-IO/P1071-LED	4进4出	2	6	1	2	4	9~36V
9	P2381Y-C6 V1.0(1135G7)	I5-1135G7/2.4G	2*SODDDR4	P112	P1082-C6/P177-IO/P1071-LED	4进4出	2	6	1	2	4	9~36V
10	P2381Y-C6 V1.0(1235U)	I5-1235U/1.3G	2*SODDDR4	P122	P1082-C6/P177-IO/P1071-LED	4进4出	2	6	1	2	4	9~36V

NOTE:1、一键还原与复位键二选一，默认一键还原，部分CPU不支持一键还原，具体联系FAE，需认复位键，要改硬件。
2、带风扇的型号是P2381F-P4/P2381F-C6

配件清单

序号	料号	描述	数量	单位	备注
1	03.02.N12-KAKOU-12	卡扣, L16.7*W16.2*H14.4mm	8	pcs	标配
2	03.03.J01-0H015-00	国标电源线_L=1.5m 品字尾	1	pcs	可选
3	03.01.DC0-L090F-90	DC12V/7.5A/90W/DC头2.5双芯/品字尾 电源适配器	1	pcs	可选



工业平板

所有产品规格变更，均不另行通知