

ITX-B330_I516L VER:1.0 (3210M)



ITX-B330_I516L VER:1.0 主板正面图



ITX-B330_I516L VER:1.0 主板 IO 图



ITX-B330_I516L VER:1.0 主板侧面图

Product model	ITX-B330_I516L VER:1.0(3317U/3210M)
processor	Integrated Intel®Core I5-3317U/3210M 1.7/2.5GHz dual-core quad-thread processor,TDP 18W
	Compatible with Intel® Sandy /Ivy Bridge Celeron/Pentium/I3/I5/I7 BGA1023 low power processors
chipset	Intel® HM76 high-speed chipset
Internal memory	1*SODDDR3 memory slot, supporting single-channel DDR3 1600/1333 memory, supporting a maximum of 8GB
display	Integrated Intel® HD Graphics4000 core graphics card, support single display, dual display mode, extended mode
	1*VGA, 2*HD OUTPUT, 1* LVDS interface, support dual channel 24bit, and EDP shared pin
network	1* RTL8111H Gigabit NIC, supports network wake up and PXE functions.
deposit	2* SATA2.0 hard disk interface, transmission rate up to 3Gbps
	1*MSATA slot, support SSD SSD,SSD transmission speed up to 6Gbps
Tone frequency	Onboard ALC262 6-channel hi-fi audio controller with MIC/Line-out support. Power amplifier
	The power amplifier is recommended to use a 4 Ω 3W speaker
expansion	1* Mini-PCIE slot, supporting WIFI, 3G/4G modules
I/O ports on the backplane	2 x USB3.0,2 x USB2.0
	1* HD OUTPUT port
	1 x VGA port
	2* RJ-45 Gigabit network interface
	1* Line out (green)
	1* Mic (red)
	1 x 12V DC_JACK input
Built-in I/O	1* LVDS interface (2*15pin), support dual channel 24bit (dual 8)

interface	1* LVDS backlight Interface (1*6pin)
	1* J_HD OUTPUT interface (2*8Pin)
	1* JVGA1 interface (1*12pin), same signal as DB15
	6* RS232 serial port (COM2/3 supports RS422/485, COM1/COM2 9pin supports live function)
	1* LPT print port (2*13pin)
	6* USB 2.0 interface (2*5pin),
	1* PS/2 Mouse and keyboard interface (1*6Pin)
	1* Front panel function buttons and indicator ports (2*5pin)
	1* Front panel audio interface (2*5pin)
	1* Power amplifier interface (1*4pin)
	1* SIM card seat
	2* hard disk power supply interface (1*4pin)
	1* 4pin DC power interface, support 12V power input and output
Fan interface	1*4pin CPU intelligent fan interface, 1*4pin system fan interface
GPIO	Supports four input/output GPIO
BIOS	32Mb Flash ROM
Guard dog	Support hardware reset function (256 level, 0~255 seconds)
Operating system	Window 7/Windows 10/Linux
Power supply type	Adopts DC 12V power supply
Operating temperature	-10℃ to 60℃
Storage temperature	-20℃ to 70℃
Working humidity	5%-95% relative humidity, no condensation
dimension	170mm * 170mm * 22mm

订购信息:

No.	Model	CPU	PCH	Frequency	Memory	VGA	HD OUTP UT	LVDS	LAN	USB	COM	485/422	Power
1	ITX-B330_I516L VER:1.0(3210M)	I5-3210M	HM76	2.5G	1*SODDDR3	1	2	2*24BIT	1*8111H	10	6	COM2/3	DC12V
2	ITX-B330_I516L VER:1.0(3317U)	I5-3317U	HM67	1.7G	1*SODDDR3	1	2	2*24BIT	1*8111H	10	6	COM2/3	DC12V