


ITX-Y410 VER:1.0 规格表



ITX-Y410 VER:1.0 主板正面图



ITX-Y410 VER:1.0 主板 I/O 图



ITX-Y410 VER:1.0 主板侧面图



Product model	ITX-Y410 VER:1.0
processor	Supports the LGA1200 10th Intel® Celeron/Pentium/Core™ i3/i5/i7/i9 processor Note: Only 10gen cpus with 6 cores of 65W and below are supported
chipset	Using Intel® H410 high-speed chipset
Internal memory	2* DDR4 SODIMM slots, supporting up to 2933 MHZ memory and up to 128GB memory
display	Integrated Intel® HD Graphics core graphics card, support DirectX12,OpenGL4.5, support 4K/60Hz display 1 x VGA port, the maximum resolution is 1920X1200@60Hz 2* HD OUTPUT port, the maximum resolution is 4096 x 2160@30Hz 1* Supports dual-channel 24bit LVDS interface Note: EDP interface can be supported, and the pin is shared with LVDS
network	1* RTL8111H Gigabit NIC chip, supports network wake up /PXE function
deposit	2* SATA3.0 hard disk interface, transmission speed up to 6Gbps
	1* M.2 slot, supporting M.2 2260/2280 SATA SSDS
Tone frequency	Onboard ALC892 7.1+2 channel high fidelity audio controller, support MIC/Line-out, power amplifier
Expansion slot	The amplifier supports 4Ω/3W dual channels
I/O ports on the backplane	1* M.2 slot, supporting the M.2 2230 WIFI module
	4* USB3.0 port
	1* HD OUTPUT port
	1 x VGA port
	1* RJ45 Gigabit network port
	1* Line-out(green),1*MIC(red)
Built-in I/O interface	1* DC12~19V power input interface
	1* JVGA port 1*12pin, same signal as VGA port



	1* LVDS interface or EDP interface 2*15pin, support dual channel 24bit
	1* backlight power supply interface 1*6pin
	1* screen brightness adjustment interface 1*4pin
	1* RS232 serial interface,
	4* USB2.0 interface 2*5pin
	1* front audio interface 2*5pin
	1* power amplifier interface 1*4pin
	2* hard disk power supply voltage port 1*4pin
	1* Front panel function button and indicator port 2*5pin
	1* DC power interface.1*4pin support DC12~19V power input and output
Fan interface	1*4pin CPU intelligent fan interface; 1*4pin system fan port
GPIO	Supports four input/output GPIO functions
BIOS	128Mb Flash ROM
Support system	Windows 10/Linux
Guard dog	Support hardware reset function (256 level, 0~255 seconds)
Power supply type	Support DC12~19V power supply
Operating temperature	-10℃ to 60℃
Storage temperature	-20℃ to 70℃
Working humidity	5%-95% relative humidity, no condensation
Size	170mm * 170mm

订购信息:



研域
YENTEK

No.	Model	Processor	Frequency	Southbridge	Memory	VGA	HD OUTP UT	DP	LVDS	LAN	USB	COM	RS485 /422	Power
1	ITX-Y410 VER:1.0	LGA1200	/	H410	2*SODDDR4	1	2	/	2ch/24bit	1*8111 H	8	1	/	DC12~19 V